

# Cherry Bomb

Cherry Bomb



## Specifications: Cherry Bomb

## Mounting hardware included

Nominal Impedance	8 ohms
Sensitivity dB @ 2.83V/1M	83.0 dB
Frequency Response ( $\pm 3$ dB)	50 Hz - 20 kHz
Frequency Response ( $\pm 10$ dB)	42 Hz - 22 kHz
Max. Program Power	100 W
Max. Continuous Power RMS	50 W
Max. Power SPL @ 1 M	100 dB
Tap Selector	Wire Leads
Transducer - Low Frequency Driver	5.25" Polypropylene Cone w/ Rubber Surround
Transducer - High Frequency Driver	.75" Dome
Colors	Brown, Red
Inputs	Wire Lead
Height (SM = Height)	673.1 mm / 26.50 in
Diameter (SM = Width)	269.9 mm / 10.63 in
Weight	7.1 kg / 15.6 lbs
Shipping Weight	7.5 kg / 16.5 lbs

## Description

The Cherry Bomb is a full-range solution for modern landscape audio.

The Cherry Bomb's patented three-way design includes a 5" dual-chamber, band-pass subwoofer, a 4" woofer, and a .75" tweeter all in one small unit. The combination of small form factor and full-range audio performance equals faster installation times: dig only one hole for every two you would normally have to dig with a standard landscape audio package! You're running less wire and making less splices now too, not to mention there is no separate subwoofer amp needed with Cherry Bombs. The patented design doesn't just save you installation time, it also sounds better: Since the low, mid and high frequencies all originate from the same location everything is equidistant from the listening location, meaning all you hear is perfectly phase-matched full-range sound. A built-in 64W transformer comes standard for 70V installations.

## Patented

## Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

## Technical Data and Specification Tools

### Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com). Technical data and downloads include: EASE™ data – 3-D polar plots. EASE™ Address – 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets – Technical information and

architectural specs for system engineers  
SoundTubeSPEC™ –  
Proprietary speaker placement software

## Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs ([www.nwaalabs.com](http://www.nwaalabs.com)) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

## Architectural Specifications

No specifications currently.

### Rockustics

8005 W 110th Street, Suite 208  
Overland Park, KS 66210  
Phone 913.663.5600  
Fax 913.663.3200  
Toll Free (855) 663-5600  
<https://rockustics.mseaudio.com>  
All SoundTube products come with a 5-year limited warranty.