

Vaddio EasylP TableMIC D

TABLETOP MICROPHONES WITH DANTE™ NETWORKED AUDIO

ORDERING INFORMATION

Black 999-85300-000 (international) White 999-85300-000W (international)

OVERVIEW

Deliver professional-quality audio into your PC system for superior conferencing experiences.

EasyIP TableMIC D microphones connect to audio systems that utilize Dante networked audio signals. Up to four EasyIP TableMIC D microphones can be paired with the popular EasyIP Mixer and AV Bridge 2x1 products for excellent room coverage.

Designed to reduce distracting noises that arise in the conference room, the microphone's solid metal base construction and engineered feet diminish table vibration noise that other table microphones experience. The top of the EasyIP TableMIC D features a capacitive touch control surface for silent button operation and a VU meter. The ability for AV Integrators to enable and disable button functionality during configuration can further simplify the end user's videoconferencing experience.

With 360-degree coverage from three unidirectional condenser microphone elements, a single EasyIP TableMIC D microphone provides excellent coverage for a small meeting room. Pair up to four microphone pods to the AV Bridge 2x1 or EasyIP Mixer to ensure coverage in larger meeting rooms. Each of the three unidirectional cardioid microphone elements in the microphone is equipped with integrated echo cancellation and Digital Signal Processing (DSP), including equalization, automatic gain control (AGC), and adaptive noise filtering. The DSP in a companion product such as the Vaddio AV Bridge 2x1 or EasyIP Mixer provides an AEC reference from the far end and applies it to individual mic elements, so conference calls are crystal-clear on both ends of the conversation.

Just connect a standard Cat-5 cable between the EasyIP TableMIC D microphone and your preferred PoE network switch (we recommend Luxul switches.) Power, control and audio are all carried over the single cable. The EasyIP TableMIC D supports cable lengths of up to 328 feet (100 meters) between the microphone and PoE network switch port. Pairing with Vaddio equipment can be done through our free Vaddio Deployment Tool and audio flows are managed through Audinate's Dante Controller application.



FEATURES

- Full 360° pickup coverage from three unidirectional condenser microphone elements
- Easy installation, plug and play design
- Echo cancellation for crystal-clear conference calls
- One TableMIC D microphone is sufficient for most meeting rooms—use two for larger rooms
- Noise-free capacitive touch control
- Connects with a network switch, like our Luxul networking switches, and pairs with the EasyIP Mixer or AV Bridge 2x1
- Can be used in Dante audio designs
- TableMIC D is optimized for all major cloudbased conferencing applications including Zoom, Microsoft teams, Google Meet and others

A brand of | legrand

COMMERCIAL AV BRANDS



Vaddio EasyIP TableMIC D

TECHNICAL SPECIFICATIONS

Frequency Response	100 Hz to 16 KHz
THD + Noise	< 0.02%
Dynamic Range	>90 dB
Power Requirements	PoE Powered, 15W allocated, 2W typical use
Operating/Storage Temperature	32°F to 104°F (0°C to 40°C)
Operating/Storage Humidity	10% to 80% (non-condensing)
Maximum Cabling Distance	Ethernet powered, connnection up to 328 ft (100 m)
Dimensions	Height: 1.43 in. (3.6 cm) Diameter: 5.05 in. (12.8 cm)
Certifications	CE Approved, FCC Approved, TAA Compliant
Warranty	3 years

Specifications are subject to change without notice

WHAT'S IN THE BOX:

- EasyIP TableMIC D microphone (black or white)
- 25' (7.6 m) cat-5 cable (black or white)
- Quick-Start Guide

THE ART OF EASY | legrandav.com

 USA
 800.572.2011
 avvaddio.support@legrand.com

 EMEA
 +31.495.580.840
 av.emea.sales@legrand.com

 APAC
 +852.2145.4099
 av.asia.sales@legrand.com