

ONE-STOP SHOP BLAST MODERN WORKSPACE



Device Mode Solution | VCH51 & WPP30

There are two solutions for device mode connection: wired with the VCH51 and wireless with the WPP30. Both solutions are quite simple: plug-and-play, without any configuration steps.



Room scheduling | RoomPanel

Yealink MeetingBar works seamlessly with Yealink RoomPanel for rooms scheduling, including the at-a-glance room details, up-to-date scheduling status, one tap for reserving meeting spaces, and colored LED bar for indicating room status.



Wireless Microphone Extension | VCM36-W

Yealink VCM36-W wireless microphone works with Yealink MeetingBar as an optional audio component. For medium to large meeting rooms, users can choose the flexible audio solution for a dedicated meeting room based on Android.

MeetingBar Specifications

Items	Yealink A20	Yealink A30
Certification - Small Rooms (Microsoft, Zoom)	●	
Certification - Medium Rooms (Microsoft, Zoom)		●
Operation System	Android 10	Android 10
Sensor	20MP	Dual-camera system with 8MP
Camera	FOV: 120° Zoom: 8X digital	Camera 1 : 8MP / 90° / 3.5X optical PTZ + 3X digital Camera 2 : 8MP / 120° / 4X digital
Maximum Encoding & Decoding capabilities	4K60	4K60
Speaker	Built-in speaker	Built-in speakers (2)
Microphone	Full duplex with built in 8 MEMS microphones	Full duplex with built in 8 MEMS microphones
Camera Privacy Cover	Electric, automatic	Electric, automatic
AI Camera Feature	Auto Framing/Speaker Tracking/Multi-focus Framing/ Picture-in-Picture/Smart Gallery	Auto Framing/Speaker Tracking/ Picture-in-Picture/Smart Gallery

Connections		
HDMI	2x HDMI-OUT (CEC supported)	
Wired content sharing	Through Yealink VCH51, easy to extend to the conf. table, HDMI & USB-C interface for different kinds of PC	
Ethernet port	10/100M/1000M	
Motion Sensor	●	
USB Ports	1x USB-A (A20) / 2x USB-A (A30)	
Line-ins	X	3.5mm line-in & out
Wi-Fi/Bluetooth	●	●
Security lock slot	●	●
Reset slot	●	●

Touch Console	Yealink CTP18
Screen	8-inch touchscreen, 1280 x 800
Flexibility	Bracket with adjustable angle: 28° ~ 50°, meets needs for difference perspectives
PoE	●Standard with a PoE adapter
Ultra Sonic Emitter	●
Wall Mounts	Standard with wall mount bracket, set up on a table or mount on a wall